


Çok Telli Çelik Halatlar / Steel Wire Ropes

EN 12385

Nufleks (Dönmeyen)



35x7 NF

1(1+6)+6(1+6)+12(1+6)+16(1+6)

Halat Çapı Rope Diameter	Birim Ağırlık Unit Weight	Minimum Kopma Kuvveti (kN) Minimum Breaking Load (MBL)	
		1770 N/mm ² IPS	1960 N/mm ² EIPS
mm	kg/m		
10,00	0,401	56,3	62,3
11,00	0,485	68,1	75,4
12,00	0,577	81,1	89,8
13,00	0,678	95,1	105
14,00	0,786	110	122
15,00	0,902	127	140
16,00	1,027	144	160
17,00	1,159	163	180
18,00	1,299	182	202
19,00	1,448	203	225
20,00	1,604	225	249
21,00	1,768	248	275
22,00	1,941	272	302
23,00	2,121	298	330
24,00	2,310	324	359
25,00	2,506	352	390
26,00	2,711	380	421
27,00	2,923	410	454
28,00	3,144	441	489
29,00	3,372	473	524
30,00	3,609	507	561
31,00	3,854	541	599
32,00	4,106	576	638
33,00	4,367	613	679
34,00	4,636	651	721
35,00	4,912	690	764
36,00	5,197	729	808
37,00	5,490	771	853
38,00	5,790	813	900
39,00	6,099	856	948
40,00	6,416	901	997

ISO 4309'a göre; RCN: 23-2 / According to ISO 4309; RCN: 23-2



Kullanım Alanları / Applications Areas



Denizcilik
Marina



Petrol Kuyuları
Oil Industry



Mühendislik
Engineering



Kule Vinç
Tower Crane



Fore Kazık
Drilling