


Çok Telli Çelik Halatlar / Steel Wire Ropes

EN 12385

Filler



6x19 F (6x25)
6(1+6+6dt+12)
ÇÖ/IWRC

Halat Çapı Rope Diameter	Birim Ağırlık Unit Weight	Minimum Kopma Kuvveti (kN) Minimum Breaking Load (MBL)	
		1770 N/mm ² IPS	1960 N/mm ² EIPS
mm	kg/m		
10,00	0,400	63,0	69,8
11,00	0,484	76,2	84,4
12,00	0,576	90,7	100,5
13,00	0,676	106,5	117,9
14,00	0,784	124	137
15,00	0,900	142	157
16,00	1,024	161	179
17,00	1,156	182	202
18,00	1,296	204	226
19,00	1,444	227	252
20,00	1,600	252	279
21,00	1,764	278	308
22,00	1,936	305	338
23,00	2,116	333	369
24,00	2,304	363	402
25,00	2,500	394	436
26,00	2,704	426	472
27,00	2,916	459	509
28,00	3,136	494	547
29,00	3,364	530	587
30,00	3,600	567	628
31,00	3,844	606	671
32,00	4,096	645	715
33,00	4,356	686	760
34,00	4,624	728	807
35,00	4,900	772	855
36,00	5,184	817	904
37,00	5,476	863	955
38,00	5,776	910	1008
39,00	6,084	958	1061
40,00	6,400	1008	1116
41,00	6,724	1059	1173
42,00	7,056	1112	1230
43,00	7,396	1165	1289
44,00	7,744	1220	1349
45,00	8,100	1276	1411
46,00	8,464	1333	1474

ISO 4309'a göre; RCN: 04 / According to ISO 4309; RCN: 04



Kullanım Alanları / Applications Areas



Mühendislik
Engineering



Madencilik
Mining



Denizcilik
Marina



Ormanlık
Forestry



Fore Kazık
Drilling



Genel Yük Kaldırma
General Lifting