


Çok Telli Çelik Halatlar / Steel Wire Ropes

EN 12385

Filler



6x19 F (6x25)
6(1+6+6dt+12)
LÖ/FC

Halat Çapı Rope Diameter	Birim Ağırlık Unit Weight	Minimum Kopma Kuvveti (kN) Minimum Breaking Load (MBL)	
		1770 N/mm ² IPS	1960 N/mm ² EIPS
10,00	0,359	58,4	64,7
11,00	0,434	70,7	78,3
12,00	0,517	84,1	93,1
13,00	0,607	98,7	109,3
14,00	0,704	114	127
15,00	0,808	131	146
16,00	0,919	150	166
17,00	1,038	169	187
18,00	1,163	189	210
19,00	1,296	211	233
20,00	1,436	234	259
21,00	1,583	258	285
22,00	1,738	283	313
23,00	1,899	309	342
24,00	2,068	336	373
25,00	2,244	365	404
26,00	2,427	395	437
27,00	2,617	426	472
28,00	2,815	458	507
29,00	3,019	491	544
30,00	3,231	526	582
31,00	3,450	561	622
32,00	3,676	598	662
33,00	3,910	636	704
34,00	4,150	675	748
35,00	4,398	716	792
36,00	4,653	757	838
37,00	4,915	800	885
38,00	5,184	843	934
39,00	5,460	888	984
40,00	5,744	935	1035
41,00	6,035	982	1087
42,00	6,333	1030	1140
43,00	6,638	1080	1194
44,00	6,950	1131	1250
45,00	7,270	1183	1307
46,00	7,596	1236	1365

ISO 4309'a göre; RCN: 04 / According to ISO 4309; RCN: 04

Kullanım Alanları / Applications Areas



Mühendislik
Engineering



Madencilik
Mining



Denizcilik
Marina



Ormancılık
Forestry



Genel Yük Kaldırma
General Lifting