


# Çok Telli Çelik Halatlar / Steel Wire Ropes

## EN 12385

### Standart



6x19 ST  
6(1+6+12)  
ÇÖ/IWRC

Halat Çapı Rope Diameter	Birim Ağırlık Unit Weight	Minimum Kopma Kuvveti (kN) Minimum Breaking Load (MBL)	
		1770 N/mm <sup>2</sup> IPS	1960 N/mm <sup>2</sup> EIPS
mm	kg/m		
6,00	0,138	22,7	25,1
7,00	0,187	30,9	34,2
8,00	0,244	37,6	41,6
9,00	0,309	47,6	52,7
10,00	0,381	58,8	65,1
11,00	0,461	71,1	78,7
12,00	0,549	84,6	93,7
13,00	0,644	99,3	110
14,00	0,747	115	128
15,00	0,857	132	146
16,00	0,975	150	167
17,00	1,101	170	188
18,00	1,234	190	211
19,00	1,375	212	235
20,00	1,524	235	260
21,00	1,680	259	287
22,00	1,844	284	315
23,00	2,015	311	344
24,00	2,195	338	375
25,00	2,381	367	407
26,00	2,576	397	440
27,00	2,777	428	474
28,00	2,987	461	510
29,00	3,204	494	547
30,00	3,429	529	586
31,00	3,661	565	625
32,00	3,901	602	666
33,00	4,149	640	709
34,00	4,404	679	752
35,00	4,667	720	797
36,00	4,938	762	843
37,00	5,216	804	891
38,00	5,502	849	940
39,00	5,795	894	990
40,00	6,096	940	1041
41,00	6,405	988	1093
42,00	6,721	1037	1146
43,00	7,045	1087	1201
44,00	7,376	1138	1257

ISO 4309'a göre; RCN: 04 / According to ISO 4309; RCN: 04



### Kullanım Alanları / Applications Areas



Madencilik  
Mining



Balıkçılık  
Fishing



Mühendislik  
Engineering



Denizcilik  
Marina



Ormancılık  
Logging



Genel Yük Kaldırma  
General Lifting