


Çok Telli Çelik Halatlar / Multi Strand Steel Wire Ropes

EN 12385

Seale



6x19 S
6(1+9+9)
LÖ/FC

Halat Çapı Rope Diameter	Birim Ağırlık Unit Weight	Minimum Kopma Kuvveti (kN) Minimum Breaking Load (MBL)	
		1770 N/mm ² IPS	1960 N/mm ² EIPS
6,00	0,134	21,0	23,3
7,00	0,183	28,6	31,7
8,00	0,230	37,4	41,4
9,00	0,291	47,3	52,4
10,00	0,359	58,4	64,7
11,00	0,434	70,7	78,3
12,00	0,517	84,1	93,1
13,00	0,607	98,7	109,3
14,00	0,704	114	127
15,00	0,808	131	146
16,00	0,919	150	166
17,00	1,038	169	187
18,00	1,163	189	210
19,00	1,296	211	233
20,00	1,436	234	259
21,00	1,538	258	285
22,00	1,738	283	313
23,00	1,899	309	342
24,00	2,068	336	373
25,00	2,244	365	404
26,00	2,427	395	437
27,00	2,617	426	472
28,00	2,815	458	507
29,00	3,019	491	544
30,00	3,231	526	582
31,00	3,450	561	621
32,00	3,676	598	662
33,00	3,910	636	704
34,00	4,150	675	747
35,00	4,398	716	791

ISO 4309'a göre; RCN: 02 / According to ISO 4309; RCN: 02

Kullanım Alanları / Applications Areas



Tramvay
Tramway



Madencilik
Mining



Balıkçılık
Fishing



Mühendislik
Engineering



Ormancılık
Forestry



Petrol Kuyuları
Oil Industry