


Çok Telli Çelik Halatlar / Multi Strand Steel Wire Ropes

EN 12385

Seale



8x19 S
8(1+9+9)
ÇÖ/IWRC

Halat Çapı Rope Diameter	Birim Ağırlık Unit Weight	Minimum Kopma Kuvveti (kN) Minimum Breaking Load (MBL)	
		1770 N/mm ² IPS	1960 N/mm ² EIPS
mm	kg/m		
8,00	0,260	40,3	44,7
9,00	0,330	51,0	56,5
10,00	0,407	63,0	69,8
11,00	0,492	76,2	84,4
12,00	0,586	90,7	100,5
13,00	0,688	106	118
14,00	0,798	124	137
15,00	0,916	142	157
16,00	1,042	161	179
17,00	1,176	182	202
18,00	1,319	204	226
19,00	1,469	227	252
20,00	1,628	252	279
21,00	1,795	278	308
22,00	1,970	305	338
23,00	2,153	333	369
24,00	2,344	363	402
25,00	2,544	394	436
26,00	2,751	426	472
27,00	2,967	459	509
28,00	3,191	494	547
29,00	3,423	530	587
30,00	3,663	567	628
31,00	3,911	606	671
32,00	4,168	645	715
33,00	4,432	686	760
34,00	4,705	728	807
35,00	4,986	772	855
36,00	5,275	817	904
37,00	5,572	863	955
38,00	5,877	910	1008
39,00	6,190	958	1061
40,00	6,512	1008	1116
41,00	6,842	1059	1173
42,00	7,179	1112	1231
43,00	7,525	1165	1290
44,00	7,880	1220	1351
45,00	8,242	1276	1413
46,00	8,612	1333	1476
47,00	8,991	1392	1540
48,00	9,377	1452	1606
49,00	9,772	1513	1673
50,00	10,175	1575	1741

ISO 4309'a göre; RCN: 04 / According to ISO 4309; RCN: 04



Kullanım Alanları / Applications Areas



Asansör
Elevator



Mühendislik
Engineering



Genel Yük Kaldırma
General Lifting