

## WH GT Korozyona Karşı Dayanıklı Manuel Zincirli Şaryo

WH GT Corrosion Protected Geared Trolley



Çalışma Yüğü WLL (t)	Ölçüler (mm) Dimensions			
	A	B	C	E
0,5	190	154	22	27
1	206	180	30	26
2	246	210	37	26
3,2	300	249	42	28
5	336	277	50	37

### Standart Aralık 1 Standard Range 1

Çalışma Yüğü WLL (t)	I Profil Genişliği I Beam Width (mm)	d Max. Genişlik d Max. Width (mm)	f Max. f Max. (mm)	Birim Ağırlık Mass (kg)
0,5	50-203	203	323	9,60
1	64-203	203	332	12,30
2	88-203	203	341	17,20
3,2	100-203	203	359	28,40
5	114-203	203	366	40,10

### Genişletilmiş Aralık 2 Extended Range 2

Çalışma Yüğü WLL (t)	I Profil Genişlik I Beam Width (mm)	d Max. Genişlik d Max. Width (mm)	f Max. f Max. (mm)	Birim Ağırlık Mass (kg)
0,5	-	-	-	-
1	64-305	305	434	13,70
2	88-305	305	443	19,00
3,2	100-305	305	461	31,20
5	114-305	305	468	44,20

