


Çok Telli Çelik Halatlar / Steel Wire Ropes

EN 12385

Warrington



8x19 W
8(1+6+(6+6))
ÇÖ/IWRC

Halat Çapı Rope Diameter	Birim Ağırlık Unit Weight	Minimum Kopma Kuvveti (kN) Minimum Breaking Load (MBL)	
		1770 N/mm ² IPS	1960 N/mm ² EIPS
mm	kg/m		
8,00	0,26	40,3	44,7
9,00	0,33	51	56,5
10,00	0,41	63	69,8
11,00	0,49	76,2	84,4
12,00	0,59	90,7	100,5
13,00	0,69	106	118
14,00	0,80	124	137
15,00	0,92	142	157
16,00	1,04	161	179
17,00	1,18	182	202
18,00	1,32	204	226
19,00	1,47	227	252
20,00	1,63	252	279
21,00	1,80	278	308
22,00	1,97	305	338
23,00	2,15	333	369
24,00	2,34	363	402
25,00	2,54	394	436
26,00	2,75	426	472
27,00	2,97	459	509
28,00	3,19	494	547
29,00	3,42	530	587
30,00	3,66	567	628
31,00	3,91	606	671
32,00	4,17	645	715
33,00	4,43	686	760
34,00	4,71	728	807
35,00	4,99	772	855
36,00	5,28	817	904
37,00	5,57	863	955
38,00	5,88	910	1008
39,00	6,19	958	1061
40,00	6,51	1008	1116
41,00	6,84	1059	1173
42,00	7,18	1112	1231
43,00	7,53	1165	1290
44,00	7,88	1220	1351
45,00	8,24	1276	1413
46,00	8,61	1333	1476
47,00	8,99	1392	-
48,00	9,38	1452	-
49,00	9,77	1513	-
50,00	10,18	1575	-
51,00	10,59	1639	-
52,00	11,01	1704	-

ISO 4309'a göre; RCN: 04 ? / According to ISO 4309; RCN: 04 ?



Kullanım Alanları / Applications Areas



Asansör
Elevator



Madencilik
Mining



Petrol Kuyuları
Oil Industry



Denizcilik
Marina



Genel Yük Kaldırma
General Lifting



Mühendislik
Engineering



Fore Kazık
Drilling