


Çok Telli Çelik Halatlar / Steel Wire Ropes

EN 12385

Warrington



8x19 W
8(1+6+(6+6))
LÖ/FC

Halat Çapı Rope Diameter	Birim Ağırlık Unit Weight	Minimum Kopma Kuvveti (kN) Minimum Breaking Load (MBL)	
		1770 N/mm ² IPS	1960 N/mm ² EIPS
8,00	0,22	33,20	36,80
9,00	0,28	42	46,50
10,00	0,34	51,90	57,40
11,00	0,41	62,80	69,50
12,00	0,49	74,70	82,70
13,00	0,58	87,60	97,10
14,00	0,67	101,60	112,60
15,00	0,77	117	129
16,00	0,87	133	147
17,00	0,98	150	166
18,00	1,10	168	186
19,00	1,23	187	207
20,00	1,36	207	230
21,00	1,50	229	253
22,00	1,65	251	278
23,00	1,80	274	304
24,00	1,96	299	331
25,00	2,13	324	359
26,00	2,30	351	388
27,00	2,48	378	419
28,00	2,67	407	450
29,00	2,86	436	483
30,00	3,06	467	517
31,00	3,27	498	552
32,00	3,48	531	588
33,00	3,70	565	625
34,00	3,93	600	664
35,00	4,17	635	703
36,00	4,41	672	744
37,00	4,66	710	786
38,00	4,91	749	829
39,00	5,17	789	873
40,00	5,44	830	919
41,00	5,72	872	965
42,00	6,00	915	1013
43,00	6,29	959	1062
44,00	6,58	1004	1112
45,00	6,89	1050	1163
46,00	7,19	1097	1215
47,00	7,51	1146	-
48,00	7,83	1195	-
49,00	8,16	1245	-
50,00	8,50	1297	-
51,00	8,84	1349	-
52,00	9,19	1402	-

ISO 4309'a göre; RCN: 06 / According to ISO 4309; RCN: 06

Kullanım Alanları / Applications Areas



Asansör
Elevator



Madencilik
Mining



Petrol Kuyuları
Oil Industry



Denizcilik
Marine



Genel Yük Kaldırma
General Lifting



Mühendislik
Engineering